

# Design Specification Sheet

## FR12 Fire Resistant Gas Box



IPS Corporation  
202 Industrial Park Lane  
Collierville, TN 38017  
(901) 853-5001

Ratings: ASTM-E814 - 1 Hour (F), 1 Hour (T)  
CAN/ULC - S115 1 Hour (F/FH), 1Hour (FT/FTH)  
ASTM-E814 - 2 Hour (F), 1.25 Hour (T)  
CAN/ULC - S115 2 Hour (F/FH), 1.25 Hour (FT/FTH)  
Firestop Device, Design No. IPS/PV 120-01



Models 82446 to 82454

### Wall Construction

- Wood Or Steel Stud
- 1 Hour firewall construction consisting of each stud face being finished with 5/8 gypsum
- 2 Hour firewall construction consisting of each stud face being finished with 2 layers of 5/8 gypsum

#### 1. Box Mounting

- Box should be fastened to stud with screws or nails
- Boxes in opposing walls are to be in separate stud cavities

#### 2. Piping

- Rigid or flexible Metallic supply
- All plumbing within the wall must be secured

#### 3. Valve Options

- CSA Listed Gas valve

#### 4. Intumescent Pad

- The IPS FR12 Series washer box is manufactured from special flame resistant resin with a UL listed intumescent pad factory installed on the back of the box.
- Excessive gaps between the box and the gypsum may be filled up to 1/2" with dry wall plaster. Gaps over 1/2" must be sealed with silicone firestop sealant applied to the depth of the gypsum.

